

SNAKKY RESTYLING



SNAKKY RESTYLING is the new aesthetically and technically renewed model of the Snakky vending machine. Perfectly suitable for medium-size locations, Snakky Restyling can offer an appealing, sturdy but elegant design, matchable with the one of Kikko Restyling:

- metal side panel
- user's interface area with black plastics
- lock fitted on the metal part

TEMPERATURE

Guaranteed temperatures at 32°C and 65% humidity:

- Uniform (5°-8°C)
- Stratified (10°-15°C snack area, 5°-7°C C&B area)

SAFETY

- Lock reinforced by a bush
- Closure by means of a sliding bar with two hooking points

ELECTRONICS

- 16 bit-electronics with in-built 4 Mb Flash Eprom
- Management of the setup files and statistical data by means of Up-Key

PAYMENT SYSTEMS

Payment systems can be easily installed in the renewed user's interface area. The presence of pre-cut panels will facilitate any kind of action in this area. Snakky Restyling is pre-set for the installation of systems with Executive and MDB protocol as well as for the installation of validators.

The following can be also fitted at the same time:

- changegiver coin mechanism / validator
- bill acceptor
- cashless system with key or card.



ACCESSORIES

- Photocell kit (as standard)
- Coin box lid kit
- Wall-fastening bracket kit
- Master / slave kit
- Lift-up kit
- Bidirectional drawer motors kit
- Keypad protection kit
- Infrared kit
- RS232 jack Kit
- GSM kit



EXAMPLES OF POSSIBLE CONFIGURATIONS

4 snack trays				6 snack trays			
12 selections / 270 products				27 selections / 338 products			
1 bottle tray							
6 selections / 36 products							
1 can tray							
6 selections / 36 products							
8	8	8	200 mm	10	10	10	200 mm
8	8	8	157 mm	13	13	13	197 mm
13	13	13	107 mm	13	13	13	157 mm
19	19	19	117 mm	13	13	13	127 mm
6	6	6	234 mm	13	13	10	134 mm
6	6	6	117 mm	10	8	8	134 mm

- Snack
- Bottles 0,5 l PET
- Cans 0,25/0,33 l

The numbers in the table indicate the product capacity

CHARACTERISTICS

Height	1700 mm
Width	707 mm
Depth	860 mm
Overall depth with door open	1335 mm
Weight	190 kg ca.
Power supply voltage	230 V
Power supply frequency	50 Hz
Absorbed power	345 W
Maximum operating conditions	32°C - 65% R.H.
* +10 - 10 mm	

POWER CONSUMPTION

For each hour of stand-by	151 Wh
Ambient temperature	20 °C
Refrigerated box temperature	8 °C

N&W GLOBAL VENDING S.p.A.

Via Roma, 24
24030 Valbrembo (BG) Italia
Tel. +39 035 606111
Fax +39 035 606519



www.nwglobalvending.com